

Technical Information

PURE[®] SLIDE SL lift & slide door system

single, double and track configurations

PURE[®]
WINDOW SYSTEMS

Scope

The PURE® SLIDE SL lift & slide doors has been designed to meet current and future building regulation, with impressive U values and thermal performances. PURE® is an evolved generation of aluminium door systems manufactured in the UK. They combine the long life and low maintenance of powder coated aluminium externally with a patent pending high insulation PUR foam thermal barrier. PURE® lift & slide doors are capable of accepting glazing up to 52mm thick depending on weight.

Materials

- All aluminium sections are extruded using Aluminium Alloy 6060 or 6063 T6 to BS EN 755 part 9 2008 or BS EN 12020-2.
- Polyamide thermal barriers are manufactured in accordance with PA66 GF25.
- Gaskets are manufactured in accordance with BS373.

Finishes

PURE® SLIDE SL lift & slide door sections are available typically in two finishes.

- Polyester Powder Coating to BS EN 12206:2004 Part 1 – painted in house. Surface finish at 40 microns standard, or enhanced to 60 microns for marine environments, in accordance with ISO 9001, ISO 14001 and ISO 18001.
- Anodised finishes are to BS3897: 1991 to a minimum of 25 microns (AA25), supplied in either satin or polished finish in a limited range of colours.

Construction

PURE® is constructed using mitred corners, joined with mechanical cleats; alignment chevrons assist in clean, accurate mitres.

A proprietary sealant is used on all metal joints in line with good practice.

Environmental

Senior Architectural Systems is fully compliant with BS EN ISO 9001, BS EN ISO 14001 and OHSAS 18001 standards.

PURE®, when used on projects involved in a BREEAM assessment, or within the Code for a Sustainable Built Environment and the Code for Sustainable Homes (which therefore involves the Green Guide to specification) can offer significant benefits. For project specific assistance, please contact our specification team.

Weather Rating

Tested to BS6375-1, BS6375-2 and BS6375-3 Annex A

Patent Number
GB252363.8

Typical* sizes

Max Door Leaf Width	3005mm
Max Door Leaf Height	2916mm
Max Outerframe Width	Project specific
Max Outerframe Height	3000mm
Max Weight Per Door Leaf (Standard Duty)	200Kg



*For guidance only – when exceeded please consult our technical department



Glazing

Thickness	28mm - 52mm
-----------	-------------

For thicker options please consult our technical department

Average U values

Standard Duty. CEN standard - Standard	2000 x 2180
 28mm Double Glazed Unit	1.56 W/m ² K
 48mm Triple Glazed Unit	1.17 W/m ² K

Standard Duty. CEN standard - Thermally Enhanced	2000 x 2180
 28mm Double Glazed Unit	1.47 W/m ² K
 48mm Triple Glazed Unit	1.08 W/m ² K

CEN Standard is based on a single and double track configuration.
For further U value calculations please contact our technical department

Security

Security tested to PAS24: 2016, security hardware required.
Q-Mark fully certified.

Specification. Please contact our national team of architectural advisors for advice on product suitability, calculations and NBS or bespoke specifications.

Senior Architectural Systems Ltd, Eland Road, Denaby Main, Doncaster, South Yorkshire, DN12 4HA.
Tel: 01709 772 600 E-mail: info@sasmail.co.uk www.seniorarchitectural.co.uk

Due to a policy of continual product development, Senior Architectural Systems Ltd reserves the right to alter any of the specifications given in this publication without prior notice. The specification for any given application must be checked with Senior Architectural Systems Ltd prior to manufacture. No responsibility for accuracy is accepted by Senior Architectural Systems Ltd.