

Contact: \_\_\_\_\_  
 Company: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 \_\_\_\_\_ Postcode: \_\_\_\_\_  
 Telephone: \_\_\_\_\_ Fax: \_\_\_\_\_  
 Mobile: \_\_\_\_\_ Email: \_\_\_\_\_

**JOB REFERENCE:** \_\_\_\_\_

COLOUR		Standard (All the same cost)	
<b>External:</b>		<b>Internal:</b>	
White Gloss		White Gloss	
Grey RAL 7016 Matt		Grey RAL 7016 Matt	
Black Matt RAL 9005		Black Matt RAL 9005	
<b>Bespoke</b> (Additional Cost)			
<b>RAL Colour:</b>	<input type="text"/>	<b>RAL Colour:</b>	<input type="text"/>

**EXTERNAL EAVES SIZES**

**Width:**  **Projection:**

**GLASS OPTIONS**

UNGLAZED	Ambi Neutral 1.2
Ambi Blue 1.2	Sunshine Blue 1.0
Ambi Aqua 1.0	Ambi Bronze 1.2
Clear Self Clean 1.2	

**OPTIONS**

**NEW** Eaves Screw Port Cover

Finials Required:  Ball  None

**SITE DELIVERY POSTCODE:** \_\_\_\_\_  
(for load calculation purposes only)


**EXTRA'S REQUIRED / NOTES:**

Draw lantern roof in plan view, please provide the **external dimensions of your upstand and the fitted water proof membrane with a recommended additional 12mm to both length and width allowing a 6mm overhang.**

## Korniche

**Korniche is a 25 degree fixed pitch.**

To complete a digital version of this form - click on the box above to upload a sketch/drawing as PDF, JPEG or PNG file.



Ring beam detail

← 69mm →