

### ORDERED BY:

Company Name: \_\_\_\_\_

Address: \_\_\_\_\_

Tel No: \_\_\_\_\_

Email: \_\_\_\_\_

Order No: \_\_\_\_\_

Your Ref \_\_\_\_\_

Delivery Date \_\_\_\_\_

### SITE CONTACT:

Company Name: \_\_\_\_\_

Delivery Address: \_\_\_\_\_

Post Code: \_\_\_\_\_

Tel No: \_\_\_\_\_

### DIMENSIONS

Overall Frame Width mm \_\_\_\_\_

Overall Frame Height mm \_\_\_\_\_

### CILL OPTIONS

Cill requirements included in the overall height


☐ No Cill

☐ 190mm Cill (Recommended for 2 Track)


☐ 230mm Cill (Recommended for 3 Track)

### Section Details

Sash Clip  
In Bead




Sash



### BOTTOM TRACK


Double Track

☐




Triple Track

☐




### MEETING STILE OPTIONS

☐ Slimline Meeting Stile, 25mm Sitaline  
(Available in Double & Triple Track options)



☐ Standard Meeting Stile, 50mm Sitaline  
(Available in Double & Triple Track options)



### 30MM ADD ON

☐

Top

☐

LH Side

☐

RH Side

### 4000MM<sup>2</sup> TRICKLE VENT

Trickle Vent through 30mm add on ☐

Colour

Quantity

### GLAZING OPTIONS

Glazing 28mm Toughened Low E Argon Filled Black  
Warm Edge Spacer as Standard

☐

Unglazed

☐

28mm Glazing 1.1 U-value

☐

44mm Triple Glazing 0.6 U-value

☐

Laminated 6.8mm outer DOC Q

### COLOUR OPTIONS

#### Standard Lead Times - Single Colours

RAL 9016 Traffic White ☐

RAL 7016 Anthracite Grey Matt ☐

RAL 9005 Black Matt ☐

Dual Colour: Anth Grey Matt/Traffic White Gloss ☐

Dual Colour: Black Matt/Traffic White Gloss ☐

#### Bespoke Colours

Single Colour - RAL No

Dual Colour - External RAL No

Dual Colour - Internal RAL No

Note: Bespoke Single / Dual Colour Orders are on an extended lead time

### HARDWARE OPTIONS

D Handle ☐



Colour:

Available in:




Coastal Pole Handle ☐



Colour:

Available in: Black or Stainless Steel

Lift & Slide Only Handle ☐



Stainless Steel

Black

### BLINDS

☐ Manual Cord

☐ Solar Powered

Colour

☐ Manual Slider

☐ Electric Powered

Please Note: Some Blind Systems may not be available due to the size of the glazing units.

### TECHNICAL INFORMATION

|                                   |             |                            |                                      |
|-----------------------------------|-------------|----------------------------|--------------------------------------|
| Market-maximum sash size          | 2.5m x 2.7m | Maximum security           | EN tested to European standards      |
| Maximum sash weight per door leaf | 250kg       | Maximum insulation U-value | 1.4 W/m <sup>2</sup> K, DER C rating |
| Interlock sightlines              | 25mm/50mm   | Maximum weatherproofing    | BS6375 Part 1: 2009                  |
| Double track outer frame width    | 120mm       | Single or dual colour      | Qualicoat factory powder coated      |
| Triple track outer frame width    | 183mm       |                            |                                      |

Inline ☐ Lift & Slide ☐

### SKETCH YOUR DOOR

○ = Fixed x = Sliding

|  |  |  |  |  |  |
|--|--|--|--|--|--|
|  |  |  |  |  |  |
|  |  |  |  |  |  |
|  |  |  |  |  |  |
|  |  |  |  |  |  |
|  |  |  |  |  |  |

### NOTES:

PART L - It is your responsibility to order the correct Glazing Specification which is specific to your project to meet current building regulations.

PART F AND O - It is your responsibility to order the correct number of Trickle vents which will give the required room ventilation to each finished product to meet current building regulations.